DEHUMIDIFIER CORPORATION OF AMERICA

R-454B REFRIGERANT

REFRIGERANT SAFETY GROUP A2L

DCA 3600Y AIR COOLED - NON WATER HEATING DEHUMIDIFIER

DCA 3600YWH WATER HEATING ASSIST DEHUMIDIFIER

PERFORMANCE







Performance	82DB / 50% R.H.	82DB / 60% R.H.	Notes
Moisture Removal, LB/HR	34.1	43.2	1
Net Sensible Cooling, MBH	51.3	45.5	2
Net Reheat, MBH	56.6	67.1	3
Water Heating, MBH (Water Heating Models Only)	109.1	113.3	4

Notes:

1. Reheat mode assuming 1050 BTU/lb
2. Cooling mode with remote condenser at 95F.
3. Defined as sum of latent and compressor input. Use dehumidifier for supplemental heat only.
4. Assuming 85F entering water temperature.
5. For conditions and data not shown contact the factory

CAUTIONS: The reheat capacity rating includes latent recovery and heat of compression. It is recommended that dehumidifier be used for supplemental heat only. The cooling capacity is based on an ambient temperature of 95°F. As outside conditions vary, so will the performance of the dehumidifier. Ratings are subject to change without notice.

DCA 3600Y AIR COOLED - NON WATER HEATING DEHUMIDIFIER

DCA 3600YWH WATER HEATING ASSIST

DESIGN SPECIFICATIONS

Electrical	208/230V	460V	575V
Phase/Hz	3/60	3/60	3/60
Compressor B.T.U.	89,900	89,900	89,900
Compressor RLA	27.6	14.1	11.6
Compressor LRA	203	98	84
Blower Motor HP	2	2	2
Blower Motor FLA	6.6	2.9	2.3
Unit FLA	35.9	17.8	14.6
Maximum Fuse Size	60	30	25
Minimum Circuit Ampacity	42.8	21.3	17.5
Operating KW	8.67	8.43	8.42

CFM.....3600

External Static Pressure.....1.00" H_2O

Refrigerant.....R-454B (Factory Charged 45 lbs.)

Compressor Type.....Scroll

DCA 3600Y Filter (Qty: 4).....16"x20"x1" Fiberglass

DCA 3600YWH Filter (Qty: 4)....20"x25"x1" Fiberglass

Drain Connection.....1" Bar Drain

DCA 3600Y Weight.....900 lbs.

DCA 3600YWH Weight.....1250 lbs.

Liquid Inlet [inches O.D.] (up to 50')[1].....0.625

Hot Gas Outlet [inches O.D.] (up to 50')[1].....1.125

Water Inlet [inches O.D.].....1.375

Water Outlet [inches O.D.] 1.375

Water Flow G.P.M.[2] 16.0

Pressure Drop (Ft. WC)[2] 9.9

[1] Over 50ft contact factory

[2] Water Flow data based on 60% RH + Return Air 82°F and Pool Water at 85°F

STANDARD FEATURES

- Listed To UL 60335-2-40
- 3 Year Part Warranty
- Single Refrigeration Circuit
- Single Scroll Compressor
- Powder Coated, Galvannealed Steel Cabinet
- Low Ambient Head Pressure Control
- Remote Condenser Ready
- Rifle Tube Refrigeration Coils
- TEFC Blower Motor
- Stainless Steel Condensate Drain Pan
- Standard Microprocessor Control System
- Motorized Evaporator Bypass Damper
- ElectroFin Coated Coils

OPTIONAL FEATURES

- Right Side Component Service Access
- Top or Bottom Discharge (Not Field Convertible)
- Extended Surface Filters 2" & 4"
- Outdoor Installation Package
- Outdoor Make Up Air Assembly with Damper & Filter
- External Static Upgrade
- Water Cooled Condenser For Water Heating Or A/C Available
- Remote Ready Delete
- Defrost Timer Package
- Control Options
- Space Heating Options Available
- Other Options Available

DCA DEHUMIDIFIER CORPORATION OF AMERICA

www.dehumidifiercorp.com

W57 N14363 DOERR WAY, SUITE 6
P.O. BOX 917
CEDARBURG, WI 53012
PHONE: 262-377-7501
E-MAIL: info@dehumidifiercorp.com